

Mini-Porter-Cyclone

MP-50SWA CF12 Specifications

2019/10/17

Item	Contents
① Hose	Soft polyvinyl chloride(ID φ 38 × 400mm)
② Lid stopper	Stainless • SUS304
③ Packing	Silicon
④ Silencer	External side: Iron(Chrome plating)/Inside: White cloth and Glass wool
⑤ Lid stopper support	Stainless • SUS304
⑥ Cyclone body	Stainless • SUS304(connection: φ 50/ plate thickness: 1.2mm)
⑦ Hose	Transparent PVC (ID φ 50 × 3000mm)
⑧ MP lid	Aluminum alloy casting • AC4C Melamine resin baking finish
⑨ Draw latch	Iron (Chrome plating) Rivet (Aluminum)
⑩ Suction pipe	Aluminum (OD φ 50 × 600mm)
⑪ Tank	Stainless • SUS304 30
⑫ Stand	Aluminum alloy casting • AC4C Melamine resin baking finish
⑬ Caster	Conductive casters/ 4 pieces (1 equipped with a brake)
⑭ フィルター	External side: Iron(Chrome plating)/Inside: Glass wool
O ring	NBR
Air pressure	0.5~0.6Mpa (5~6kg/cm ²)
Vaccum	20.6~24.8kpa (2,101~2,529mmAq)
Air consumption	240~280 /min Normal

Remarks

