

# Mini-Porter-Cyclone

## MP-50WA CF12 Specifications

2010/10/23

Item	Contents
① Hose	Soft polyvinyl chloride(ID φ 38 × 400mm)
② Lid stopper	Stainless • SUS304
③ Packing	Silicon
④ Silencer	External side: Iron(Chrome plating)/Inside: White cloth and Glass wool
⑤ Lid stopper support	Stainless • SUS304
⑥ Cyclone body	Stainless • SUS304(connection: φ 50/ plate thickness: 1.2mm)
⑦ Hose	Transparent PVC (ID φ 50 × 3000mm)
⑧ MP lid	Aluminum alloy casting • AC4C Melamine resin baking finish
⑨ Draw latch	Iron (Chrome plating) Rivet (Aluminum)
⑩ Suction pipe	Aluminum (OD φ 50 × 600mm)
⑪ Tank	Transparent PVC 25 ℓ
⑫ Stand	Aluminum alloy casting • AC4C Melamine resin baking finish
⑬ Casters	Conductive casters/4 pieces (1 with a break)
⑭ Filter	External side: Iron(Chrome plating)/Inside: Glass wool
O ring	NBR
Air pressure	0.5~0.6MPa(5~6kg/cm <sup>2</sup> )
Suction power	20.6~24.8kpa(2101~2529mmAq)
Air consumption	240~280 ℓ /min Normal

Remarks

