

Mini-Porter-Cyclone

MP-38SWA CF12 Specifications

2019/10/16

Item	Contents
① Hose	Soft polyvinyl chloride(ID ϕ 38 \times 400mm)
② Lid stopper	Stainless \cdot SUS304
③ Packing	Silicon
④ Silencer	External side: Iron(Chrome plating)/Inside: White cloth and Glass wool
⑤ Lid stopper support	Stainless \cdot SUS304
⑥ Cyclone body	Stainless \cdot SUS304(connection: ϕ 38/ plate thickness: 1.2mm)
⑦ Hose	Transparent PVC (ID ϕ 38 \times 3000mm)
⑧ MP lid	Aluminum alloy casting \cdot AC4C Melamine resin baking finish
⑨ Draw latch	Iron (Chrome plating) Rivet (Aluminum)
⑩ Suction pipe	Aluminum (OD ϕ 38 \times 600mm)
⑪ Tank	Stainless \cdot SUS304 30
⑫ Stand	Aluminum alloy casting \cdot AC4C Melamine resin baking finish
⑬ Caster	Conductive casters/4 pieces (1 with a break)
⑭ Filter	External side: Iron(Chrome plating)/Inside: Glass wool
O ring	NBR
Air pressure	0.5~0.6MPa (5~6kg/cm ²)
Vaccum	20.6~24.8kpa (2,101~2,529mmAq)
Air consumption	240~280 /min Normal

Remarks

