

Silent-Cleaner

SC60-32SVG Specifications

2011/02/15

Item	Contents
① Hose connection	3/8" ball valve + air coupler
② Air filter	Stainless•SUS304 Wire mesh screen (40mesh)
③ Pressure gauge	An air pressure gauge at the time of the use.
④ Cleaner lid	Aluminum alloy • AC4C Melamine resin baking finish
⑤ Hose	Transparent PVC (ID ϕ 32×2000mm)
⑥ Clasps	Iron (Chrome plating) Rivet (Aluminum)
⑦ Suction pipe	PVC (OD ϕ 32×700mm)
⑧ Tank	Stainless •SUS304 60 ℓ
⑨ Stand	Iron (Chrome plating)
⑩ Casters	2 rubber casters/1 conductive caster equipped with a break
O ring	NBR
Air pressure	0.5~0.6MPa (5~6kg/cm ²)
Suction power	-0.0502~-0.0597MPa (5020~5970mmAq)
Exhaust sound	60dB (0.5MPa (5kg/cm ²))
Air consumption	555~647 ℓ / min Normal
Weight	18.5kg

Remarks

- This model is used specially for adhesive materials like grease.
- More than 0.37MPa(3.7kg/cm²) air pressure③ is required for operation.

