

Silent-Cleaner

SC30-32SVG Specifications

2011/02/15

Item	Contents
① Hose connection	3/8" ball valve + air coupler
② Air filter	Stainless•SUS304 Wire mesh screen (40mesh)
③ Pressure gauge	An air pressure gauge at the time of the use.
④ Cleanerlid	Aluminum alloy • AC4C Melamine resin baking finish
⑤ Hose	Transparent PVC (ID ϕ 32×2000mm)
⑥ Clasps	Iron (Chrome plating) Rivet (Aluminum)
⑦ Suction pipe	PVC (OD ϕ 32×600mm)
⑧ Tank	Stainless •SUS304 30 ℓ
⑨ Stand	Aluminum alloy resin •AC4C Melamine resin baking finish
⑩ Casters	Conductive casters / 4pieces (1 equipped with a break)
O ring	NBR
Air pressure	More than 0.5MPa (5kg/cm ²)
Exhaust sound	60dB (0.5MPa (5kg/cm ²))

Performance	Air pressure	Suction power	Air consumption
	0.5Mpa (5kg/cm ²)	-0.0502 (5020mmAq)	555 ℓ /min Normal
	0.6Mpa (6kg/cm ²)	-0.0597 (5970mmAq)	647 ℓ /min Normal
	0.7Mpa (7kg/cm ²)	-0.0657 (6570mmAq)	739 ℓ /min Normal

Remarks

- This model is used specially for adhesive materials like grease.
- More than 0.37MPa(3.7kg/cm²) air pressure③ is required for operation.

